

For Sale



- ◆ TOTAL turn key solution.
- ◆ The complete installation conforms to AS 4024-1 & 2, AS 1219 & EN954-1, Safe guarding.
- ◆ Safety system conforming to Category 4.
- ◆ Light guards at front of press (vertical and horizontal)
- ◆ Sides & rear mesh guarding
- ◆ Parallel responsibility which includes a machine handover document.
- ◆ 12 month 24/7 warranty.
- ◆ Oils, grease, installation and commissioning.

Press Shop Automation
LEADERS IN METAL STAMPING TECHNOLOGY





Press Shop Automation

LEADERS IN METAL STAMPING TECHNOLOGY

CHIN FONG PRESS			
ITEM	SPECIFICATION	ITEM	SPECIFICATION
Model	G2-160V	MPC-3130 control	Standard
Capacity	160 ton	Overrun detector	Standard
Rated Tonnage (above BDC)	6 mm	Monitored Dual Solenoid Valve	Standard
Stroke length	1200 mm	Die Height indicator	Standard
Speed	30—55 spm	Total counter	Standard
Die Height	450 mm	Maintenance counter	Standard
Slide adjustment	100 mm	Hydraulic overload device	Standard
Bolster area (LR x FB)	2000 mm x 760 mm	Power shut off	Standard
Bolster thickness	150 mm	Motorized slide adjust	Standard
Slide area (LR x FB)	1600 mm x 550 mm	Automatic Grease Lubrication	Standard
Main Motor	VS 20HP x 4P	Pre set counter	Standard
Slide adjust motor	1HP x 4P	Life counter	Standard
6 spare Electronic cams	Standard	Air Ejector	Standard
Miss feed detector	Standard	VS Drive	Standard
Mechanical slide knock out	Standard	Anti Vibration pads	Standard
Foot switch	Standard	Tee Stand	Standard
Main Motor Reverse switch	Standard	Oils and Grease	Standard
PRESS GUARDING			
Model	'SICK' C-4000	Category	4
Resolution	14 mm	Length	900mm vertical, 300mm hori-
Position	At front of press	Mesh guards	Both sides and rear (under flywheel)

Other inclusions:

- Electrical and mechanical integration
- 12 months warranty 24/7
- All electrics and controls are monitored by a safety control system making the entire line conform to AS 4204-1 and 2 AS1219, EN954-1 and category 4
- Training
- Manuals, electrical, mechanical & pneumatic
- Cranes to off load and position

Exclusions are: Insurance for off loading, relocation of other machines, removal of old oil containers, foundations & concreting costs, mains electrical supply to the press location (this must meet AS3000), mains pneumatic connection to the press location, & mains power transformers.

Press Shop Automation
Unit 1, 2 Heald Road,
Ingleburn NSW 2565

Ph: 02 9605 7628
Fax: 02 9605 6126

Enquiries:
sales@press-shop.com.au

Press Shop Automation
Unit 17,
7—21 Garden Boulevard
Dingley Village, Vic 3172

Ph: 03 9551 6733
Fax: 03 9551 6744